

INDUTTANZE A FUNGHETTO

Induttori radiali con pin inseriti nel corpo di ferrite
Tolleranza induttanza + - 10%

CODICE	INDUTTANZA microHenry	CORRENTE A	DIMENSIONI A GIORNO			
			A	B	C	D
FU001	2500	0.1	6	8.5	3	4
FU002	3.3	1.5	6	8.5	3	4
FU003	6	0.4	6	8.5	3	4
FU004	10	2	8	10	5	5
FU005	18	2	8	10	5	5
FU006	22	1	8	10	5	5
FU007	27	1	8	10	5	5
FU008	33	1.5	8	10	5	5
FU009	47	1	8	10	5	5
FU010	100	0.5	8	10	5	5
FU011	120	1	8	10	5	5
FU012	220	0.5	8	10	5	5
FU013	330	0.5	8	10	5	5
FU014	680	0.4	8	10	5	5
FU015	1000	0.3	8	10	5	5
FU016	3900	0.1	8	10	5	5
FU017	4500	0.1	8	10	5	5
FU018	4700	0.15	8	10	5	5
FU019	33	2	9	12	5	7
FU020	50	1	9	12	5	7
FU021	100	0.5	9	12	5	7
FU022	100	1	9	12	5	7
FU023	120	2	9	12	5	7
FU024	150	1.5	9	12	5	7
FU025	220	1	9	12	5	7

