




s.r.l.

avvolgimenti lineari e toroidali


PCB MOUNTING POWER MODULE

FEATURES

- Input Range 100-240Vac 50/60Hz
- Output range from 3.3V-24Vdc, also can be customized
- Encapsulated design prevent dust and humidity
- Self-Extinguishing Plastic 94V-0
- High efficiency, Low temperature rise
- Low standby power (< 0.15W) and leakage current
- Integrated EMC network
- Dielectric Strength: 3600Vac 5mA 1min
- Integrated perfect Protection
 - OLP: Output over load protection
 - OSP: Output short protection
 - OTP: Over temperature protection
- Compact size and light weight (< 40g)
- UL-60950 / IEC-60950 Compliance




OUTLINE DIMENSIONS



Suffix:P
Vo: Pin 7-9
Ground : pin 9

Suffix:N
Vo: Pin 9-7
Ground : pin 7



Recommended Drill-hole Diameter for 1.3mm pins



s.r.l.

avvolgimenti lineari e toroidali


ELECTRONIC SPECIFICATIONS

Suffix : P Ground @ pin 9


Suffix : N Ground @ pin 7

Model	GC30SM3V3P	GC30SM5V0P	GC30SM12VP	GC30SM15VP	GC30SM24VP
Maximum power (Ta = 40°C)	4.5W	4.5W	5W	5W	5W
	2.0W	2.5W	2.5W	2.5W	2.5W
Output voltage	3.3V	5.0V	12V	15V	24V
Output voltage Accuracy	±5%	±5%	±5%	±5%	±5%
Ripple voltage (max)	< Vout * 5%				

POWER DERATING



Ambit temperature



Input voltage